

VISUAL COMFORT & Co.

96116S-32: 12V Clear T3 Festoon 2700K LED Lamp



Dimensions:

Diameter: 0.47"
Length: 1.62"

Bulb Appearance: Clear - Glass Lens

Bulb Type: T3

Bulb Type: Festoon

Volts: 12

Watts: 0.6556

Watts Consumed: 0.6556

Watts Rated: 0.6556

Hours Rated: 50000

Lumens: 59

Bulb Temp: 2700 °K

CRI: 80

Features:

- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.

Material List:

Safety Listing:

Safety Listed for Damp Locations
Safety Listed for Damp Locations

Instruction Sheets:

English (HC-1715FS)

Collections: Lx LED Festoons (Primary)
Lx Components

Upgrade to our Lx LED Festoons from our 5w Xenon Festoons and realize an energy savings of over 80% without compromising light output. Lx LED Festoons are dimmable on magnetic and electronic low voltage systems. For magnetic systems, a standard incandescent or magnetic low voltage (MLV) dimmer can be used. For electronic, an electronic low voltage (ELV) dimmer is recommended.

Applications: Task & accent lighting for undercabinet, coves, toe-kick spaces and so much more. Directional nature of LED is ideal for in-cabinet lighting.

Retrofit/Remodel Installations for Magnetic Transformer Systems - JUST REPLACE THE LAMP! Compatible as a retrofit for existing Lx Xenon lamp and compatible Xenon lamp systems. Note: The unique design of the PCB (Printed Circuit Board) makes over voltage due to under capacity a non-issue.

Product Features: Ease of installation. Ease of retrofit/remodel. Bendable/flexibility of the system.

Dimmability: Dimmable with standard incandescent dimming switch.

A "Fit & Forget" Solution: Offering 35,000 hours of useful life (equivalent to 30 years at 20 hours of use per week)

Efficacy: 83 Lumens/Watt

LED Festoon Product Line Options & Features: Warm (3000K) and Warmer (2700K) CCT; Clear lens for optimal performance; Frosted lens to reduce glare; 3 Year Warranty

UPC #:785652198601

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Fr. Class	UPS Ship
Individual	96116S-32	1	785652198601	2.0	2.0	0.5	0.0	0.01	0	Yes
Master Pack	96116S-32	500	10785652198608	13.5	11.25	11.75	1.03	12.4	0	Yes
Shipping Master	96116S-32	500	20785652198605							No
NJ Pallet		25000		48.0	40.0	67.5	75.0	635.0		No
NV Pallet		25000		48.0	40.0	70.0	77.78	635.0		No